

Compact Hydraulic Licence plate press



Features

- Easy to use, insert embossing frame, automatic start
- Ideally suited for Euro plates (52 x 11 cm) with border
- Pressure adjustable from 5 to 35 ton
- Light weight, normal table is usually sufficient


SINCE 1843

Benefits

- Easy maintenance, simple construction
- Own JKG development, many years of experience combined in one machine
- Safety built in, limited hub, limit switches, emergency stop

Technical specifications

Type :	P-JKG02/230 or P-JKG02/400
Pressure :	5 to 35 ton (30 to 220 bar)
Dimensions (WxHxD) :	835 x 640 x 330mm
Press opening :	560 x 65mm
Press hub :	max. 40mm
Effective press area :	540 x 200mm
Embossing frame width :	550mm
Weight :	280 kg (without aggregate)
Mains voltage :	220 - 240V 50 Hz (1 phase)
Power (max.) :	1,1 kW
or	
Mains voltage :	380V - 400V 50 Hz (3 phase)
Power (max.) :	1,5 kW



www.jkg.eu

J. Knieriem B.V.
A. Fokkerstraat 20
NL - 4462 ET Goes
T: +31 113 250500
F: +31 113 231762
E: info@jkg.eu



Bij Koninklijke Beschikking Hofleverancier
By Appointment to the Court of the Netherlands
Fournisseur de la Cour par ordonnance Royale
Durch Königlichen Erlass Hoflieferant

